



Europäisches  
Patentamt

European  
Patent Office

PH DE 03038A

Office européen  
des brevets

REC'D 20 DEC 2004

WIPO

PCT

Bescheinigung

Certificate

Attestation

Die angehefteten Unterla-  
gen stimmen mit der  
ursprünglich eingereichten  
Fassung der auf dem näch-  
sten Blatt bezeichneten  
europäischen Patentanmel-  
dung überein.

The attached documents  
are exact copies of the  
European patent application  
described on the following  
page, as originally filed.

Les documents fixés à  
cette attestation sont  
conformes à la version  
initialement déposée de  
la demande de brevet  
européen spécifiée à la  
page suivante.

IB/04/52430

Patentanmeldung Nr. Patent application No. Demande de brevet n°

03104290.6

**PRIORITY  
DOCUMENT**  
SUBMITTED OR TRANSMITTED IN  
COMPLIANCE WITH RULE 17.1(a) OR (b)

Der Präsident des Europäischen Patentamts;  
Im Auftrag

For the President of the European Patent Office

Le Président de l'Office européen des brevets  
p.o.

R C van Dijk



Anmeldung Nr:  
Application no.: 03104290.6  
Demande no:

Anmeldetag:  
Date of filing: 20.11.03  
Date de dépôt:

Anmelder/Applicant(s)/Demandeur(s):

Philips Intellectual Property & Standards  
GmbH  
Steindamm 94  
20099 Hamburg  
ALLEMAGNE  
Koninklijke Philips Electronics N.V.  
Groenewoudseweg 1  
5621 BA Eindhoven  
PAYS-BAS

Bezeichnung der Erfindung/Title of the invention/Titre de l'invention:  
(Falls die Bezeichnung der Erfindung nicht angegeben ist, siehe Beschreibung.  
If no title is shown please refer to the description.  
Si aucun titre n'est indiqué se référer à la description.)

A method for direct communication between a first station and a second station of  
a wireless network

In Anspruch genommene Priorität(en) / Priority(ies) claimed /Priorité(s)  
revendiquée(s)  
Staat/Tag/Aktenzeichen/State/Date/File no./Pays/Date/Numéro de dépôt:

Internationale Patentklassifikation/International Patent Classification/  
Classification internationale des brevets:

H04L12/28

Am Anmeldetag benannte Vertragstaaten/Contracting states designated at date of  
filing/Etats contractants désignées lors du dépôt:

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LU MC NL  
PT RO SE SI SK TR LI

**DESCRIPTION****A METHOD FOR DIRECT COMMUNICATION BETWEEN A FIRST STATION  
AND A SECOND STATION OF A WIRELESS NETWORK**

The invention relates to a method for direct communication between a first station and  
5 a second station in an Access Point controlled wireless network, wherein one channel  
communication is ruled by an identifier associated with the Access Point.

In an Independent Basic Service Set (IBSS), defined for example in the IEEE 802.11  
standard, all communicating stations communicate directly to each other. In an  
10 infrastructure Basic Service Set (BSS), all stations associated to a common Access  
Point (AP) communicate via this Access Point. Therefore, in such a BSS, all data are  
sent twice, since the first station sends its data to the Access Point whereupon the  
Access Point must forward all data of the first station destined for the second station, as  
no direct communication is possible. This fact reduces the overall throughput of the  
15 BSS and increases delay. Existing Access Points are not able to allow direct  
communication between their associated stations. An upgrade of the software of the  
Access Point to incorporate direct communication is sometimes not possible or  
desirable, for example in the case that an Access Point base is already installed.

20 A method to allow communication between two stations is disclosed in WO 01/15387.

It is object of the invention to provide for direct station-to-station communication in a  
centrally organized network that does not require any changes in the Access Point.

25 This object is solved by a method as defined in claim 1 and a network as defined in  
claim 9.

In an Access Point controlled wireless network, wherein one channel communication is  
ruled by an identifier associated with the Access Point, a method for direct

communication between a first station and a second station according to the invention comprises the steps of:

- 5       - generating a second identifier by said first station, different from the identifier associated with the Access Point, and optionally choosing a second channel;-  
          sending, by said first station, an invitation method for direct communication carrying said second identifier to said second station;
- sending, by said second station, a response message acknowledging the invitation message;
- 10     - setting up direct communication between said first station and said second station using said second identifier.

The invention therefore foresees that stations which want to communicate directly use a special network identifier and optionally a different channel for that purpose. The  
15   stations agree upon this special network identifier and the channel by a hand-shake message exchange prior to the direct communication. The Access Point, which does not know the special network identifier, will interpret the direct data packets as belonging to a foreign network and will refrain from forwarding the data. When communicating with another station in the infrastructure-based network, a station always uses the  
20   infrastructure BSS identifier, but when communicating directly with a station, the second identifier is used.

The invitation message and said response message can be sent via the Access Point using the identifier associated therewith. An alternative is to exchange said invitation  
25   message and said response message directly between said first station and said second station using an identifier different from the identifier associated with the Access Point.

The response message may contain information that said second identifier is confirmed or that said second identifier is rejected and a third identifier is proposed. This third  
30   identifier is again different from the identifier associated with the Access Point.

For direct communication between stations, a dedicated identifier may be created.

Optionally, the response message may contain information the proposed channel is confirmed or that the channel is rejected and a different channel is proposed.

5

Even though the two types of communication might operate on the same communication channel, they should not collide if carrier sensing is applied. If two communications with different identifiers do collide, a collision resolution has to be applied. An example for such a protocol is the IEEE 802.11 standard. Therefore, the invention is very well suited for such system.

10

The invention will be explained in further detail with reference to the accompanying drawings, wherein

15    Figure 1    illustrates a first embodiment of the invention to establish direct communication between two stations of an infrastructure based network as initiated from a first station;

Figure 2    illustrates the acknowledgement of an invitation by a second station;

20    Figure 3    illustrates a second embodiment of the invention, where direct communication is established without involvement of the Access Point;

Figure 4    illustrates the acknowledgement of the invitation received from a first station by the second station; and

Figure 5    illustrates a successful direct communication between two stations.

25    In Figure 1, two stations STA1 and STA2 are associated to the Access Point AP of an infrastructure-based Basic Service Set BSS. The BSS identifier equals the MAC address of Access Point AP. When stations STA1 and STA2 want to set up a directing connection, they have to agree upon the identifier and optionally a different channel for their communication. To do this, station STA1 sends an invitation frame or invitation message to the Access Point AP, where the invitation message includes all necessary information for the intended side traffic which then avoids involvement of the Access

30

Point AP. The Access Point AP copies the message and forwards it to stations STA2.

As shown in Figure 2, station STA2, upon receipt of the invitation message, sends a response message to the Access Point AP acknowledging the invitation, confirming the  
5 identifier and channel for direct communication. Optionally, station STA2 rejects a proposed identifier and/or channel and proposes a new identifier and/or channel to station STA1, where again the identifier has to be different from the identifier associated with the Access Point AP. Again optionally, station STA2 can also propose an identifier and/or channel for further direct communication. The response message is  
10 forwarded by the Access Point AP to station STA1.

Figure 3 shows a second embodiment wherein station STA1 invites station STA2 to the direct communication by using a special identifier, preferably the second identifier, and optionally a second channel, and sends the invitation frame via a side traffic. This  
15 invitation message may or may not include a proposal for another identifier and/or channel for further direct communication. If the second identifier is a dedicated identifier, station STA2 will recognize that the invitation message is a direct link message and send, as illustrated in Figure 4, the response message directly to the station STA1 without involving Access Point AP.

20

In both embodiments, station STA1 and station STA2 agree upon a BSS identifier that is different from the one of the infrastructure based network. In case that station STA2 has already agreed on an identifier and channel with still another station, station STA2 may propose to use this identifier and channel also for communication with station  
25 STA1.

After successful agreement on direct communication, the initiating station STA1 has to test the link. Station STA1 then established the direct communication via a successfully transmitted frame.

5

Figure 5 shows that station STA1 and STA2 have successfully established direct communication using the second identifier and optionally the second channel. Station STA1 and station STA2 are still associated to the Access Point AP, and when communicating via Access Point AP, they will use the identifier and channel associated therewith. Principally, all stations participating in the Access Point controlled wireless network can have one or several direct connections owing to the fact that each sub-network refrains from communication during the active intervals of the other network.

10

**CLAIMS**

1. In an Access Point controlled wireless network, wherein one channel communication is ruled by an identifier associated with the Access Point, a method for direct communication between a first station and a second station, comprising the steps of:

- 5       - generating a second identifier by said first station, different from the identifier associated with the Access Point, and optionally choosing a second channel;
- sending, by said first station, an invitation message for direct communication carrying said second identifier and optionally said second channel to said second station;
- 10       - sending, by said second station, a response message acknowledging the invitation message;
- setting up direct communication between said first station and said second station using said second identifier and optionally said second channel.

15   2. The method according to claim 1, wherein said invitation message and said response message are sent via the Access Point using the identifier associated therewith.

      3. The method according to claim 1, wherein said invitation message and said response message are exchanged directly between said first station and said second station using  
20   an identifier different from the identifier associated with the Access Point.



4. The method according to claim 1, wherein said response message contains information that said second identifier is confirmed or that said second identifier is rejected and a third identifier is proposed, wherein said third identifier is different from the identifier associated with the Access Point.
5. The method according to claim 4, wherein said response message according to claim 4 contains information that said second channel is confirmed or that said second channel is rejected and the channel which is associated with the Access Point or a third channel is proposed.
6. The method according to claim 1, wherein said second identifier is a dedicated identifier for direct communication between stations.
7. The method according to claim 1, wherein carrier sensing is applied to avoid collision on said channel.
8. Use of the method according any of claims 1 to 7 in the communication protocol of the IEEE 802.11 standard.

9. An access point controlled wireless network, wherein one channel communication is ruled by an identifier associated with the access point, said network comprising at least a first station and a second station capable to established direct communication,

5 wherein:

said first station generates a second identifier, different from the identifier associated with the access point, and optionally chooses a second channel and sends an invitation message for direct communication carrying said second identifier and optionally said second channel to said second station;

10

said second station sends a respond message acknowledging the invitation message;  
and

15

said first station sets up direct communication with said second station using said second identifier and optionally said second channel.

**ABSTRACT****A METHOD FOR DIRECT COMMUNICATION BETWEEN A FIRST STATION  
AND A SECOND STATION OF A WIRELESS NETWORK**

- 5 In an Access Point controlled wireless network, wherein one channel communication is ruled by an identifier associated with the Access Point, a method for direct communication between a first station and a second station, comprises the steps of:
- 10 - generating a second identifier by said first station, different from the identifier associated with the Access Point, and optionally choosing a different channel;
  - sending, by said first station, an invitation message for direct communication carrying said second identifier and optionally said second channel to said second station;
  - 15 - sending, by said second station, a response message acknowledging the invitation message;
  - setting up direct communication between said first station and said second station using said second identifier and optionally said second channel.




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5